

DATE	SYM	REVISION RECORD	AUTH.	DR.	CK.
3/05	-	INITIAL RELEASE	.	WJR	

ADJUSTMENT SCREW, SEE PERFORMANCE CURVE FOR APPROX. INITIAL SETTING

TIGHTEN SET SCREW WITH 1/16" ALLEN WRENCH TO SECURE ADJUSTMENT.

#18 AWG X 10" LONG  
.032 PVC INSULATION

15/32-32 2A THD

.115 TRAVEL

1 1/2

2 3/16

Ø1 1/2

- 4. CONSTRUCTION: ANODIZED ALUMINUM HOUSING;  
STAINLESS STEEL PLUNGER.
- 3. FORM Z CONTACT CONFIGURATION
- 2. SWITCH: 5 AMP 125 VAC

NOTES: 1. WIRES: #18 AWG X 10" LG, 2 WHITE (N.D.)  
2 RED (N.C.).

TOLERANCES (EXCEPT AS NOTED)	
DECIMAL	± -
FRACTIONAL	± -
ANGULAR	± -

**HIGHPOWER**

SECURITY PRODUCTS, LLC

290 PRATT STREET, 4TH FLOOR, MERIDEN, CT 06450

FORM "Z" WIRED PNEUMATIC SWITCH	SCALE 1:1	DRWN. WJR	APPR.
DATA SHEET - PNEUMATIC SWITCH, FORM Z			
DATE 3/17/05	DRAWING NUMBER 750-1000		REV. -